

(中)

標稱 截面積	芯線數	導體		絕緣 厚度	被覆 厚度	完成 外徑 (約)	導體電阻 (20℃)	試驗電壓	絕緣電阻 (20℃)	
		組成 線數/單線 徑	外徑						PE	PVC
Mm	C	No./mm	mm	mm	mm	mm	Ω/km	kv/1min	MΩ-km	
14	2	7/39/0.26	5.1	1.4	1.5	19.0	1.33	2	1500	40
	3	7/39/0.26	5.1	1.4	1.5	20.0	1.33	2	1500	40
	4	7/39/0.26	5.1	1.4	1.6	23.0	1.33	2	1500	40
	5	7/39/0.26	5.1	1.4	1.6	25.0	1.33	2	1500	40
	6	7/39/0.26	5.1	1.4	1.7	27.5	1.33	2	1500	40

(英)

Nominal Cross Sectional Area	Core	Conductor		Insulation thickness (average)	Oversheath Thickness (average)	Overall Diameter (approx.)	Max. Conductor Resistance (20℃)	A.C. Voltage Test	Min. Insulation Resistance (20℃)	
		Composi- tion*	Dia. approx.						PE	PVC
mm	C	No./mm	mm	mm	mm	mm	Ω/km	kv/1min	MΩ-km	
14	2	7/39/0.26	5.1	1.4	1.5	19.0	1.33	2	1500	40
	3	7/39/0.26	5.1	1.4	1.5	20.0	1.33	2	1500	40
	4	7/39/0.26	5.1	1.4	1.6	23.0	1.33	2	1500	40
	5	7/39/0.26	5.1	1.4	1.6	25.0	1.33	2	1500	40
	6	7/39/0.26	5.1	1.4	1.7	27.5	1.33	2	1500	40