

PVC Insulated Wire

UL STYLE NO. 1028

UL File No.E50032

StandardUL Subject 758

UseInternal Wiring of Appliances.

Rating

STYLE No.	Volt.(max.)	Temp.(max.)
UL STYLE No.1028	600V	105°C

Construction



Wire Size (AWG)	Conductor		PVC Insulation		Standard Length m(ft.)
	Stranding (No./mm)	Diam. (mm)	Nominal Thickness (mm)	Overall Diam. (Approx.) (mm)	
22	1/0.643	0.643	1.15	2.95	305(1000)
	**7/0.25	0.75	1.15	3.05	
	17/0.16	0.76	1.15	3.05	
20	1/0.813	0.813	1.15	3.10	305(1000)
	**7/0.32	0.94	1.15	3.25	
	26/0.16	0.94	1.15	3.25	
	21/0.18	0.95	1.15	3.25	
18	1/1.024	1.024	1.15	3.30	305(1000)
	16/0.26	1.20	1.15	3.50	
	34/0.18	1.21	1.15	3.50	
16	1/1.29	1.29	1.15	3.60	305(1000)
	26/0.26	1.50	1.15	3.80	
	52/0.18	1.50	1.15	3.80	
14	1/1.63	1.63	1.15	3.95	305(1000)
	41/0.26	1.90	1.15	4.20	
12	1/2.05	2.05	1.15	4.35	305(1000)
	42/0.32	2.40	1.15	4.70	
	65/0.26	2.40	1.15	4.70	
10	1/2.59	2.59	1.15	4.90	305(1000)
	105/0.26	3.20	1.15	5.50	
8	133/0.283	4.00	1.25	6.50	305(1000)

Note: **Top-coated conductors are available.