

PVC Insulated Cable

UL STYLE NO. 1571

UL File No. E50032

Standard UL Subject 758

Use Internal Wiring of Class 2 Circuits in Electronic Equipment.

Rating	STYLE No.	Volt.(max.)	Temp.(max.)
	UL STYLE No.1571	30V	80°C

Construction



Conductor			PVC or SRPV Ins.		Shield		PVC Jacket		Standard
Wire Size (AWG)	Stranding (No./mm)	Diam. (mm)	Nominal Thickness (mm)	Diam. (mm)	Approx. (No./mm)	Diam. (mm)	Nominal Thickness (mm)	Diam. (mm)	Length m(ft.)
30	1/0.254	0.254	0.20	0.65	23/0.10	0.85	0.25	1.35	610(2000)
	• 7/0.10	0.30	0.20	0.70	24/0.10	0.90	0.25	1.40	610(2000)
28	1/0.32	0.32	0.21	0.75	26/0.10	0.95	0.25	1.45	610(2000)
	• 7/0.127	0.38	0.21	0.80	27/0.10	1.00	0.25	1.50	610(2000)
26	1/0.404	0.404	0.20	0.80	27/0.10	1.00	0.25	1.50	610(2000)
	• 7/0.16	0.48	0.21	0.90	30/0.10	1.10	0.25	1.60	610(2000)
24	1/0.511	0.511	0.22	0.95	32/0.10	1.15	0.25	1.65	610(2000)
	• 7/0.20	0.60	0.22	1.05	34/0.10	1.25	0.25	1.75	610(2000)
	11/0.16	0.61	0.22	1.05	34/0.10	1.25	0.25	1.75	610(2000)
22	1/0.643	0.643	0.22	1.10	36/0.10	1.30	0.25	1.80	610(2000)
	• 7/0.25	0.75	0.22	1.20	39/0.10	1.40	0.25	1.90	610(2000)
	17/0.16	0.76	0.22	1.20	39/0.10	1.40	0.25	1.90	610(2000)
20	1/0.813	0.813	0.22	1.25	40/0.10	1.45	0.25	1.95	610(2000)
	• 7/0.32	0.94	0.23	1.40	45/0.10	1.60	0.25	2.10	610(2000)
	26/0.16	0.94	0.23	1.40	45/0.10	1.60	0.25	2.10	610(2000)
	21/0.18	0.95	0.23	1.40	45/0.10	1.60	0.25	2.10	610(2000)

Note: 1 * Top-coated conductors are available.

2. Wire Size No. 50 AWG Min. is available in UL standard.