

and Jacketed Cord

UL STYLE NO. 2096

CSA TYPE TR-64

UL File No. E50032

CSA File NO. LL48503

Standard UL Subject 758, CSA C22.2 No.16

Use Internal Wiring of Appliances and Electronic Equipment.

Rating

STYLE No.	Volt.(max.)	Temp.(max.)
UL STYLE No.2096	300V	80°C
CSA-TYPE TR-64	300V	90°C

Construction



No. of Cond.	Conductor			PVC Insulation		Twisting Diam. (mm)	Shield		PVC Jacket		Standard Length m.(ft.)
	Wire Size (AWG)	Stranding (No./mm)	Diam. (mm)	Min. Avg. Thickness (mm)	Diam. (Approx.) (mm)		Approx. (No./mm)	Diam. (mm)	Min. Avg. Thickness (mm)	O.D. (Approx.) (mm)	
2	* 30	1/0.254	0.254	0.38	1.15	2.30	60/0.10	2.50	0.38	3.40	305(1000)
		7/0.10	0.30	0.38	1.20	2.40	62/0.10	2.60	0.38	3.50	
2	28	1/0.32	0.32	0.38	1.20	2.40	62/0.10	2.60	0.38	3.50	305(1000)
		7/0.127	0.38	0.38	1.25	2.50	64/0.10	2.70	0.38	3.60	
2	26	1/0.404	0.404	0.38	1.30	2.60	67/0.10	2.80	0.38	3.70	305(1000)
		7/0.16	0.48	0.38	1.35	2.70	58/0.12	2.94	0.38	3.85	
2	24	1/0.511	0.511	0.38	1.40	2.80	60/0.12	3.04	0.38	3.95	305(1000)
		7/0.20	0.60	0.38	1.50	3.00	64/0.12	3.24	0.38	4.15	
		11/0.16	0.61	0.38	1.50	3.00	64/0.12	3.24	0.38	4.15	
2	22	1/0.643	0.643	0.38	1.55	3.10	67/0.12	3.35	0.38	4.25	305(1000)
		7/0.25	0.75	0.38	1.65	3.30	67/0.13	3.55	0.38	4.45	
		17/0.16	0.76	0.38	1.65	3.30	67/0.13	3.55	0.38	4.45	
3	26	1/0.404	0.404	0.38	1.30	2.80	69/0.13	3.05	0.38	3.95	305(1000)
		7/0.16	0.48	0.38	1.35	2.91	65/0.14	3.19	0.38	4.10	
3	24	1/0.511	0.511	0.38	1.40	3.02	67/0.14	3.30	0.38	4.20	305(1000)
		7/0.20	0.60	0.38	1.50	3.23	63/0.16	3.55	0.38	4.45	
		11/0.16	0.61	0.38	1.50	3.23	63/0.16	3.55	0.38	4.45	

Note: * Wire Size No. 30AWG is not available in CSA Standard.